

# AZTEC OILS LTD

## TECHNICAL DATA SHEET

### SYNTHETIC FE 0w/30

A FULLY SYNTHETIC super multigrade oil based on fully synthetic base stocks and formulated with the very latest in advanced technology, producing a super high performance engine oil which delivers excellent Fuel Economy.

SYNTHETIC FE 0w/30 replies to the demands of present day motoring conditions by affording the highest level of performance and engine protection in the most severe conditions at both high and low ambient temperatures.

#### Benefits

- Effective fuel efficiency
- Excellent high and low temperature performance
- Exceptional long term anti-wear characteristics
- Very high standard of engine cleanliness
- Long lasting dispersant performance and corrosion protection
- Excellent sludge control for stop go city motoring
- High temperature protection against ring sticking, maintaining oil performance, reduced oil consumption and emissions

#### Application

SYNTHETIC FE 0w/30 is primarily designed for use where an up to date light viscosity multigrade engine oil is required as is recommended by various engine manufacturers in order to meet the performance requirements necessary of use in up to date multi-valve engines.

API SL/CF ACEA A3,B3,B4  
MB 229.5  
VW502.00, 505.00

BMW LL-01  
ILSAC GF-3

#### Typical Test Data

SG @ 15.6°C	0.875
KV @ 100°C (cSt)	10.0
KV @ 40°C (cSt)	55
VI	168
Flash Point (°C)	220
TBN (mgKOH/g)	9
Cold Crank @ -35°C	5500 Cp

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers