

AZTEC OILS LTD

FULL SYNTHETIC 5w/30

TECHNICAL DATA SHEET

Product Description:

Fully Synthetic 5W/30 is a new generation fully synthetic super multigrade engine oil formulated using the latest developments in synthetic technology together with the most up to date advancements in additive chemistry setting new standards in engine oil performance.

Fully Synthetic 5W/30 has been developed to enable outstanding performance to be provided along with effective emission control and full compatibility with emission control after treatment systems. Low SAPS (sulphated ash phosphorus and sulphur) additive technology ensure optimum performance of emission control equipment including particulate filters, at the same time providing long term emission system protection, ensuring a high level of continuous pollution control thereby minimising environmental damage.

Applications:

Fully Synthetic 5W/30 is particularly formulated to meet the performance demands and requirements of the most up to date BMW Longlife-04 specification and Daimler Chrysler MB 229.31 which encompass high standards of emission control under all conditions including vigorous high speed styles of driving.

Health & Safety: (Group 1)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers

Benefits:

- Effective environmental protection
- Ensures lubricant performance over extended drain intervals
- Effective fuel efficiency
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability
- Excellent high and low temperature performance
- Exceptional long term additive response

Product Specification:

API	SM
ACEA	A3/B4-04, C3-04, A3/B4-02
BMW	Longlife-04
MB	229.31

Typical Test Data:

KV @ 100°C (cSt)	11.8
KV @ 40°C (cSt)	72.3
Viscosity index	160
CCS @ -30°C (cP)	6080
Sulphated ash (% w/w)	0.773
TBN (mg KOH / g)	7.8
Flash Point COC (°C)	212