

AZTEC OILS LTD

HD Engine Oils

Aztec HD Oils are a range of engine oils manufactured from solvent refined paraffinic base oils blended with anti oxidant & corrosion inhibitors and suitable for static non turbo charged diesel engines and small petrol units.

Application:

Naturally aspirated diesel engines up to API CC

Petrol engines requiring performance level up to API SE

Performance Level:

API CC/SE, Mil-L-46152, Allison C3,

Caterpillar TO-2.

Typical Properties:

| | 10w | HD 20w | 30 | 40 |
|--|------------|-------------------|-----------|-----------|
| SAE Viscosity Grade | 10w | 20w | 30 | 40 |
| Specific Gravity @: 15.oC | 0.873 | 0.878 | 0.885 | 0.892 |
| Kinematic Viscosity mm ² /S | | | | |
| @40oC | 37.0 | 61.0 | 92.0 | 134.0 |
| @100oC | 6.1 | 8.2 | 10.7 | 13.9 |
| Viscosity Index (VI) | 108 | 100 | 98 | 98 |
| Pour Point oC | -25 | -22 | -19 | -19 |
| Total Base Number mg KOH/gm | 7.5 | 7.5 | 7.5 | 7.5 |
| Sulphated Ash % wt | 1.0 | 1.0 | 1.0 | 1.0 |

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers