

AZTEC OILS LTD

UTTO - HYTRAN

Description

Hytran is a top quality hydraulic – transmission fluid, specifically designed for use in agricultural tractor power transmission – hydraulic systems, inboard wet brakes and rear axles, employed in the majority of modern farm tractors, agricultural machinery and some construction equipment.

This fluid is formulated from the highest quality base oils, together with a special performance package and shear stable viscosity modifiers, providing an advanced lubricant which demonstrates excellent performance characteristics against the various stringent test requirements of major equipment manufacturers.

Features

- Superior oxidation stability
- Outstanding rust and corrosion protection
- Excellent wet brake, anti-squawk and chatter suppression
- Exceptional anti-wear and extreme pressure properties
- Excellent high and low temperature performance
- Low foaming tendency and good seal compatibility

Performance

John Deere JD 303, JD20A, JD20B, JD20C, J14B
Ford ESN-M2C, 86A/E, M2C-159A, M2C-134, A/B/C/D
Massey Ferguson MF1135, MF1139, MF1143, MF1127A
Allison C-4, Caterpillar T0-2, API GL4/CRC N20
Denison HF-0, HF-1, HF-2
Sperry Vickers M230-S, M2950S
Hanomag, Volvo BM, JCB

Typical Physical Properties

Kinematic Viscosity @ 100oC	10.3
Kinematic Viscosity @ 40oC	60
Viscosity Index	125
Flash point closed (oC)	195
Density @ 15oC	0.887
Pour Point (oC)	-40

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers