

# AZTEC OILS LTD

## BENTONE 2 grease

Aztec Bentone grease is a premium quality grease for use in all extreme temperature situations.

### Features

1. Good Mechanical stability
2. Good oxidation stability
3. Good water resistance
4. Good oil separation
5. Wide temperature range

This smooth textured grease has outstanding heat resistance since its thickener will not melt. The consistency of the grease remains constant throughout a wide temperature range. This grease is an organo modified clay dispersed in a mineral oil, interpreted by IARC as being non carcinogenic.

### Typical Physical Characteristics

Appearance	_____	Short fibred grease
Colour	_____	Brown
Unworked penetration	_____	265-295
Worked penetration	_____	265-295
NLGI classification	_____	No. 2
Dropping point (IP50)	_____	Infusible
Oil separation (IP121)	_____	2%
Oxidation stability (IP142) 168 hrs @ 99oC pressure drop	_____	3 psi
Copper corrosion (IP112)	_____	Negative
Alluminium corrosion (Mod IP112)	_____	Negative
Mild steel corrosion (Mod IP112)	_____	Negative
Water washout (ASTM D1264) @ 30oC	_____	5%
@ 79oC	_____	11%
Ventmeter pressure @ 70oF	_____	550 psi

**Health & Safety** Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers