

# AZTEC OILS LTD

## RockDrill Oils

### Description

Aztec Oils **RockDrill Oils** are specially designed products for the lubrication of heavy duty percussion and rotary pneumatic tools such as road breakers, rock drills etc.

Special attention has been paid to selection of the base oil which provides maximum freedom from “Waxing” and gives a very low pour point. Additives have been incorporated to ensure good emulsifying and load carrying properties in order to give effective lubrication under both low and high ambient temperatures and under wet or dry conditions. They also ensure adequate protection against rusting and corrosion.

NB: this grade is not suitable for light or high speed pneumatic equipment such as hand drills, nut runners etc.

### TYPICAL PHYSICAL PROPERTIES

| ROCKDRILL               | T32  | T46  | T100 | T150 | T220  | T320 |
|-------------------------|------|------|------|------|-------|------|
| Relative Density @ 15oC | 0.88 | 0.88 | 0.89 | 0.89 | 0.895 | 0.90 |
| Viscosity Cst @ 40oC    | 32   | 46   | 100  | 150  | 220   | 320  |
| Viscosity Cst @ 100oC   | 5.3  | 6.7  | 11.2 | 14.4 | 23    | 31.4 |
| Viscosity Index         | 95   | 95   | 95   | 98   | 100   | 100  |
| Closed Flash Point oC   | 225  | 230  | 245  | 245  | 245   | 235  |
| Pour Point oC           | -18  | -18  | -18  | -19  | -20   | -15  |

**Health & Safety** Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers