

AZTEC OILS LTD

COMPRESSOR OILS

DESCRIPTION

A range of premium quality industrial compressor lubricants. Aztec Compressor range is blended from special base oils which have low carbon forming tendencies and are fortified with additives to inhibit wear, corrosion, oxidation and foaming.

ADVANTAGES

Minimizes the risk of a compressor explosion by only forming low levels of soft carbon in the critical high temperature discharge zone.

Prolonged service life due to good oxidation resistance, excellent anti-wear and anti-corrosion properties.

Low foaming tendency.

Good demulsifiability.

APPLICATION

Suitable for use in rotary screw, vane and reciprocating compressors.

PERFORMANCE LEVEL: DIN 51506 VDL

PROPERTIES

	Aztec Compressor Oils				
	32	46	68	100	150
ISO Viscosity Grade	32	46	68	100	150
Specific Gravity at 16 oC	0.870	0.875	0.878	0.883	0.888
Kinematic Viscosity mm ² /S					
at 40 OC	32.0	46.0	68.0	100.0	150.0
at 100 oC	5.4	6.8	8.7	11.5	15.2
Viscosity Index (VI)	102	100	100	100	100
Pour Point OC	-20	-20	-20	-20	-20
Flash Point C.O.C CC	230	230	235	245	255

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers