

AZTEC OILS LTD

Rust Preventive LT

DESCRIPTION:

A solvent deposited, water displacing, wax film corrosion preventive which is truly a multipurpose product with application in many sectors of industry and ideal for use where the storage conditions cannot be controlled. e.g. Overseas shipment, outdoor storage or unheated warehouses.

PROPERTIES:

Rust Preventive LT can be used as a replacement for conventional vehicle underseals, its resilience and self healing properties gives superior protection against weather and aggressive environments.

Rust Preventive LT can also be used on timber and plywood used in the construction of containers, caravans, boats and external structures, where the exclusion of moisture and prevention of warping is required.

APPLICATION.

Rust Preventive LT can be dipped, brushed or sprayed. 20 - 250C is the recommended application temperature. Residual film can be removed by common hydrocarbon solvents.

TECHNICAL DATA:

Appearance:	Dark Brown Slightly Thixotropic Liquid.
Odour:	Solvent.
Specific Gravity @ 20oC:	0.83+/- 0.02
Protection -	Indoors: 5 Years. Covered Outdoors: 3 Years. Outdoors: 1 Year.
Non-Volatile Content:	30% +/- 2%
Flash Point (COD):	40oC
Film Type:	Firm Handleable Wax.
Film Thickness:	27 Microns @ 20oC (Dipped).
Covering Capacity:	20 Square Metres/Litre.
Drying Time:	Approximately 40 Minutes.

A blend of petroleum sulphanates de-watering agents, hydrocarbons waxes, hydrocarbon solvents, coupling agents and soaps. May affect some rubbers and plastics on long term storage in its original form.

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers