

AZTEC OILS LTD

TECHNICAL DATA SHEET

Performance 10W/40 SL/CH4

Performance 10W/40 SL/CH4 is a high performance multigrade engine oil, meeting the latest API classifications. Present day motor engineering and motoring conditions have necessitated the rapid advancement in lubricant design and performance.

Performance 10W/40 SL/CH4 is a new generation multigrade engine oil manufactured from carefully selected base oils and the very latest additive technology. It meets the majority of the latest engine manufacturers requirements and specifications. It can be confidently supplied for most mixed fleet applications. Superior dispersant additives help maintain engine cleanliness in the latest petrol engines and the latest detergent additives help reduce unwanted deposits in turbo charges and on pistons.

Benefits

- High shear stability for stay in grade performance
- Excellent high temperature stability
- Improved bore polishing protection
- Excellent anti wear performance for reduced engine wear
- Ideal mixed fleet lubricant
- Excellent sludge control for stop-go city motoring

Application

Performance 10W/40 SL/CH4 is suitable for normally aspirated and turbo charged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment. It is miscible with all synthetic and mineral based engine oils.

Product Specification

Typical Test Data

API	SL/CH-4	SG @ 15.6°C	0.888
ACEA	A3,B3,B4,E2	KV @ 100°C (cSt)	13.82
VW	505	KV @ 40°C (cSt)	95.51
MB	228.1, 229.1	VI	147
Mack	EO-L	Flash Point COC (°C)	220
MAN	271	Pour Point (°C)	-32
MTU	Type 1	TBN (mgKOH/g)	9.18
Volvo	VDS		

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all of our customers